

2008



"Strobe Marks" Stop Turning At The Right Torque



TORQUE CHART

Authorized Dealer

Reorder Codes / Part Numbers

Table with columns: Part Numbers, Size, Torque (ft. lbs.), Tool Color. Includes 1/2" Drive and 3/4" Drive sections.

Table with columns: Part Numbers, Size, Torque (ft. lbs.), Tool Color. Includes 1" Drive section.

Table with columns: Part Numbers, Size, Torque (ft. lbs.), Tool Color. Includes 1" Drive section.

Table with columns: Wheel Name, Size, Torque (ft. lbs.), Tool Color.

Table with columns: Wheel Name, Size, Torque (ft. lbs.), Tool Color. Includes HEAVY DUTY APPLICATIONS section.

Main table for AUTOMOTIVE vehicles, including ACURA, AUDI, BMW, BUICK, CADILLAC, CHEVROLET/GEO, CHRYSLER, DAEWOO, DODGE, EAGLE/JEEP, FIAT, FORD, HONDA, HYUNDAI.

Main table for INFiniti, ISUZU, JAGUAR, KIA, LEXUS, LINCOLN, MASERATI, MAZDA, MERCEDES, MINI COOPER, MITSUBISHI, NISSAN/DATSUN, OLDSMOBILE, PLYMOUTH, PONTIAC, PORSCHE, SAAB, SATURN, SCION.

Main table for SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO, LIGHT TRUCKS AND VANS, ACURA, BMW, BUICK, CADILLAC, CHEVROLET/GMC, HONDA, HUMMER, HYUNDAI, INFINITI, ISUZU, JEEP, KIA, LAND ROVER.

Main table for LEXUS, LINCOLN, LEXUS, MAZDA, MERCEDES, MERCURY, NISSAN/DATSUN, OLDSMOBILE, PONTIAC, PORSCHE, SATURN, SCION, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO.

Main table for LEXUS, LINCOLN, LEXUS, MAZDA, MERCEDES, MERCURY, NISSAN/DATSUN, OLDSMOBILE, PONTIAC, PORSCHE, SATURN, SCION, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO.

Note: Every possible precaution has been taken in compiling the above list of the most popular vehicle makes and models. Neither the manufacturer nor the supplier can be held responsible for damage which might occur due to errors in the list or subsequent changes in specifications by vehicle manufacturers.

FIND A MISTAKE? CALL (800) 762-6002 www.accutorq.com

PART NO. ACC-10-0103

CAUTION: Only those instructed in the safe and proper use of AccuTorq should use them. Actual line pressure should be 90 to 100 psi and output of the air impact gun: Automotive 1/2" dr. - 150-250 ft.lbs. Med Duty Truck 3/4" dr. - 360-590 ft.lbs. Heavy Duty Truck 3/4" & 1" dr. - 650-1,000 ft.lbs. ALWAYS wear safety goggles when using AccuTorq. NEVER hold with hands while tightening. NEVER use torque sockets to remove lug nuts. When tightening lug nuts, use the criss-cross wheel nut tightening sequence.